

ZAP Telemaster S

Safe and flexible: height-adjustable platform with peripheral railing for safe standing, easy to move and folds to compact dimensions.

Product description

- Large standing surface, 665 × 440 mm, made of 7-ply adhesive-bonded plywood board, with guardrail and knee bar, ensures maximum work safety and comfortable standing.
- Simple height adjustment according to the push-up ladder principle, allowing different heights to be reached with only one platform ladder.
- Complies with new European standard DIN EN 131-7.
- Can be easily pushed thanks to two wheel assemblies, even when erected.
- Very easy to erect - handrails and guard rails are automatically unfolded during erection.
- Compact dimensions when folded, therefore easy to transport and store.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Can be used on steps / stairs.
- Order No. 41325 without stabiliser.
- Number of ballast weights required when used in an outdoor area: 4x (Order No. 41331).



Product features

Guardrail height: 1 m
 Length: 0.4 m
 Load: max. 150 kg
 Platform length: 665 mm
 Platform material: 7-layer laminated plywood
 Platform width: 440 mm
 Producttype: Flanged telescopic platform ladder
 Tray: Aluminium
 Tread depth: 30 mm
 Warranty: 10 years
 standards-pf: EN 131-7

Product variants

Order number	Dimensions, folded	Footpoint, stabiliser rod extended L x W	Footpoint, stabiliser rod retracted L x W	Height including railing	No. of rungs incl. platform	Platform height	Transport dimensions
41325	0,4 m × 2,16 m × 1,02 m	1,45m × 1 m	1,45m × 1 m	max. 2.37 m	5	0,81m / 1,08m / 1,34m	2.160 mm × 1.020 mm × 400 mm
41326	0,4 m × 2,44 m × 0,81 m	1,8m × 2,25 m	1,8m × 0,81 m	max. 2.86 m	7	1,05m / 1,3m / 1,6m / 1,83m	2.440 mm × 820 mm × 400 mm



Order number	Dimensions, folded	Footpoint, stabiliser rod extended L x W	Footpoint, stabiliser rod retracted L x W	Height including railing	No. of rungs incl. platform	Platform height	Transport dimensions
41327	0,4 m x 2,72 m x 0,81 m	2,2m x 2,55 m	2,2m x 0,81 m	max. 3.38 m	9	1,31m / 1,6m / 1,8m / 2,1m / 2,35m	2.720 mm x 820 mm x 400 mm
41328	0,4 m x 3,28 m x 0,81 m	2,8m x 2,5 m	2,8m x 0,81 m	max. 4.17 m	12	1,83m / 2,12m / 2,38m / 2,65m / 2,9m / 3,15m	3.280 mm x 820 mm x 400 mm

Order number	Weight	Width	Width extended	Width retracted	Working height	closed length	extended length
41325	28 kg	2.16 m	1 m	1 m	3.34 m	1.45 m	1.45 m
41326	34 kg	2.44 m	2.25 m	0.81 m	3.83 m	1.8 m	1.8 m
41327	38.5 kg	2.72 m	2.55 m	0.81 m	4.35 m	2.2 m	2.2 m
41328	50 kg	3.28 m	2.5 m	0.81 m	5.15 m	2.8 m	2.8 m